

1. Identification of the Substance/Preparation and the Company/Undertaking

1.1. Product identifier

Substance or preparation trade name: Parweld Tip Dip
Unique reference numbers(s): WR6050

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Welding Nozzle protection

1.3. Details of the supplier of the safety data sheet

Company/undertaking name & address: Parweld Ltd, Long Bank, Bewdley, Worcs, UK
ABN: 95 000 029 729
Telephone number: +00 44 1299 266800
Telefax: +00 44 1299 266900
Emergency telephone number: +00 44 1299 266800

1.4. Emergency telephone number

Emergency tel: +00 44 1299 266800 (office hours only)

2: Hazards identification

2.1. Classification of the substance or mixture

No Significant Hazard

2.2. Label elements

Signal words:

Precautionary statements:

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance

3. Composition/information on ingredients

3.2. Mixtures

Vegetable fat. Vaseline - a chemically pure substance. Free of chlorine and silicone.

Petrolatum (N) 90-100%
CAS 8009-03-8
EINECS 232-373-2

4: First aid measures

4.1. Description of first aid measures

Skin contact: May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact: May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Ingestion: May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

Inhalation: May cause irritation to mucous membranes. Move the exposed person to fresh air.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat

Delayed / immediate effects: Immediate effects can be expected after short-term exposure

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic and obnoxious fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes

6. Accidental release measures

Personal precautions	Ensure adequate ventilation of the working area..
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of soapy water.

7. Handling and storage

Handling	Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Do not expose to frost. Store in correctly labelled containers.

8. Exposure Controls

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	safety spectacles



9. Physical and chemical properties

Appearance:	Physical form: Paste Appearance: Pink Odour: Neutral
-------------	--

Important relevant safety parameters:

	Value	Unit	Test method (67/548/EEC)
Coagulation point	+25	°C	DIN ISO 3016
Flame point	295	°C	DIN ISO 2592
Relative density (20°C)	0.92	g/cm ³	DIN 51 757
Solubility (20°C)	not soluble		
pH value (20°C), 5%	----		
Viscosity (40°C)	Paste	mm ² /s	DIN 51 562
Ignition Temperature	480	°C	

10. Stability and reactivity

Material Safety Data



Stable under normal conditions.

11. Toxicological information

Humans: Slightly hazardous in case of skin contact (irritant), of ingestion, of inhalation.

12. Ecological information

No data is available on this product.

13 Disposal Considerations

General information	Dispose of in compliance with all local and national regulations.
Disposal methods	Contact a licensed waste disposal company. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
Disposal of packaging	Empty containers can be sent for disposal or recycling.

14. Transport information

The product is not classified as dangerous for carriage.

15. Regulatory information

None

16. Other Information

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.

Maximum content of VOC 0 g/l